Product family datasheet

OSRAM

LEDriving FL PSX24W





Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



Ultra compact LED replacement for conventional PSX24W fog lamps as socket solution Easy installation with optimized compatibility



New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps with state-of-the-art LED technology. The color temperature of 6,000K provides for a stylish cool white look and improved visibility.

Product family datasheet

Technical data

	Product information		General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global order reference	Nominal voltage	Nominal wattage
LEDriving FL \triangleq PSX24W	FL ≜ PSX24W Mainly used for headlight/ fog light applications		2604CW	12.0 V	6 W
		Photometric Data		Physical Attributes & Dimensions	Lifetime Data
Product description	Test voltage	Luminous flux tolerance	Nominal luminous flux	Diameter	Lifespan Tc
Product description LEDriving FL ≜ PSX24W	Test voltage	flux		Diameter 18.0 mm	

			(REACh)		
Product description	Lifespan B3	Technology	Date of declaration	Primary article identifier	Declaration no. in SCIP database
LEDriving $FL \triangleq PSX24W$	2500 hr	LED	21-10-2024	4062172058346 4062172058360 4062172401852	In work

Product family datasheet

File

Download Data

7

Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.LEDriving CANBUS CONTROL UNIT (LEDCBCTRL102) avoids error messages on the board computer when using LED fog lights within 21 W applicationsRefer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





1. 0 O

2. ⊂=[] ⇔ [







