OSRAM

LEDguardian ROAD FLARE





2 in 1
Can be used as a warning light and as a torch



360 degree rotationThe 360-degree rotating orange warning light function is visible from a great distance



Magnetic mounting
Thanks to the magnet
function and the hook, the
LED warning light can be
attached in various ways.



3x AAA batteries included
Operational readiness. With
the three AAA batteries
supplied, the warning light is
ready for use immediately
after purchase

Product family datasheet



Light is safety-See and be seen with OSRAM

Be prepared with OSRAM warning and safety lights. The LEDguardian ROAD FLARE is a compact LED warning light for various situations on the road and for minor inspection work on your vehicle. The 360 degrees rotating, orange, warning light function of the LEDquardian ROAD FLARE is visible from a great distance and can provide crucial information about a dangerous situation in an emergency. A total of 16 highquality long-life LEDs offer three different operating modes: 360 ° rotating orange warning light function, permanent orange light function and a white torch function. In addition, the LEDquardian ROAD FLARE impresses with its non-slip, dirt-repellent surface, a practical hook for attachment and is so robust and resistant that it can even be run over by a car** without losing performance. The LEDguardian ROAD FLARE has been tested and validated in our certified environmental simulation laboratory for extreme external influences in terms of water, dust and impact from falls. According to the IP54 & IK07 protection classes, the LEDquardian ROAD FLARE is resistant to water, dust and impacts. With the three AAA batteries supplied, the warning light is ready for use immediately after purchase. OSRAM provides a 2-year guarantee on this product* The LEDguardian ROAD FLARE is not approved as a warning light in Germany in the sense of the German Road Traffic Licensing Regulations (StVZO). Please observe any special requirements and laws in countries outside Germany regarding the use and operation of an additional warning light in road traffic.*For precise conditions please refer to: www.osram.com/am-guarantee **Tested at a mid-range car at walking pace

Product family datasheet

Technical data

	Product infor	mation	General Produ	ıct	Electrical Dat	a	
Product description	Application (Category and Product specific)		Global order reference		Nominal voltage		Nominal wattage
LEDguardian ROAD FLARE	Warning and lights	safety	LEDSL303		4.5 V		1 W
	Photometric	Data				Physica Dimens	l Attributes & ions
Product description	Color temper	Color temperature		Nomina flux	l luminous	Height	
LEDguardian ROAD FLARE	6500 K		Flash: orange/amb er / Torch:	75 lm		111.0 m	nm
			white				
							Colors & materials
•	Width		Length		Product weig	ht	Base color
Product description LEDguardian ROAD FLARE	Width 101.0 mm				Product weig 176.00 g	ht	
•		Addition	Length			ht Capabilit	Base color Black
LEDguardian ROAD FLARE	101.0 mm	Addition Scope of	Length 111.0 mm al product data	Type of B	176.00 g		Base color Black ies
•	101.0 mm Lifetime Data		Length 111.0 mm al product data		176.00 g	Capabilit	Base color Black ies
LEDguardian ROAD FLARE Product description	Lifetime Data Guarantee	Scope of Yes	Length 111.0 mm al product data	Type of B Alkaline al & Regula ccording A	176.00 g attery atory Informat rt. 33 of EU	Capabilit Technolo	Base color Black ies
LEDguardian ROAD FLARE Product description	Lifetime Data Guarantee 2 years Certificates 8	Scope of Yes	Length 111.0 mm al product data battery Environmenta Information a	Type of B Alkaline al & Regula ccording A C) 1907/2	176.00 g attery atory Informat rt. 33 of EU	Capabilit Technolo LED ion	Base color Black ies

Product family datasheet

Legal advice

* for precise conditions please refer to: www.osram.com/am-guarantee**Tested at a mid-range car at walking pace

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.